

Product:

Aluminum Foil Tape (AFT) & Foil Scrim Kraft Tape (FSK) & Aluglass Tape

Description:

Aluminum Foil Tape: A dead soft Aluminum foil of 30 microns thickness coated with highly aggressive rubber/ solvent/ acrylic based sensitive adhesive. High peel adhesion even at high temperatures. It is backed with Silicone Paper.

Foil Scrim Kraft Foil Tape: FSK which has Aluminum foil on top with Glass scrim reinforcement and kraft paper which gives rigidity is coated with solvent base pressure sensitive adhesive and laminated with Release liner.

Aluglass Tape: FSK which has Aluminum foil on top with Glass scrim reinforcement and glass cloth.



Application:

- 1) **Duct Insulation** as "Vapor Retarder" in refrigeration and air conditioning
- 2) As **heat reflector**
- 3) To **join foil faced & rock wool**
- 4) **Sealing of Double-glazing units**

Specification:

Sr. No.	Product Code	Type	Total Thickness (micron)	Adhesion to Steel (g/25mm width)	Testing Method	Type of Adhesive
1	AFT01	Aluminium Foil Tape	55	900	ASTMD-1000	Rubber/ Solvent/ Acrylic
2	AGT01	Aluglass Tape	130	850	ASTMD-1000	Solvent
3	FSK01	Foil Scrim Kraft	190	1000	ASTMD-1000/ PSTC	Solvent

* Custom sizes are available as per customers requirement

** More detailed technical specifications can be provided on request

Note:
 All statements, technical information, recommendations are based on tests conducted internally. The Seller/Supplier cannot be responsible for the misuse of its product, nor for the consequences of the usage for non-recommended applications. Always ensure that the surface of the application tape is clean and free from dust and oil. Before using, user should determine the suitability of the product for its intended use.