



ALUMINUM

FOIL TAPE

Aluminum Foil Tape: A dead soft Aluminum foil of 30 microns thickness coated with highly aggressive rubber/solvent/acrylic based sensitive adhesive. High peel adhesion even at high temperatures. It is backed with Silicone Paper.

- Duct Insulation as "Vapor Retarder" in refrigeration and air conditioning
- As heat reflector
- To join foil faced & rock wool
- Sealing of Double-glazing units





and kraft paper which gives rigidity is coated with solvent base pressure sensitive adhesive and laminated with Release liner.

Aluglass Tape: FSK which has Aluminum foil on top with Glass scrim reinforcement and glass cloth.

SPECIFICATIONS:

S.No	Product Code	Туре	Total Thickness (Micrones)	Adhesion to Steel (gram/25mm width)	Testing Method	Type Of Adhesive
1.	AFT01	Aluminium Foil Tape	55	900	ASTMD-1000	Rubber/ Solvent/ Acrylic
2.	AGT01	Aluglass Tape	130	850	ASTMD-1000	Solvent
3.	FSK01	Foil Scrim Kraft	190	1000	ASTMD-1000/ PSTC	Solvent

* Custom sizes are available as per customers requirement









^{**} More detailed technical specifications can be provided on request